

TECHNICAL DATASHEET

ITEM	DESCRIPTION
Number of test bay slots	Configured for 1 bay.
Multiple assays	Supports multiple Actim test types and protocols.
Measurement technology	Advanced image acquisition and analysis.
Modes	Timed reading and manual reading.
Illumination type	610nm red LED.
Colour Touch Screen	3.4" diagonal TFT LCD.
Communications	Ethernet for data transfer or printing. USB for data export, barcode reader and printer.
Data storage	High capacity on-board storage can store up to 999 test results. History Records allow for search and retrieval. Archive or export via USB/Ethernet.
Power	12 V DC from external AC/DC supplied plug pack. Input: 100~240V~50/60Hz 0.4A Battery power (optional). DC Voltage fluctuation $\pm 10\%$ DC Current consumption: 0.2A DC typical @ 12V DC
Dimensions	123 mm x 113 mm x 109 mm
Weight	Approx. 600 g
Printer support	Postscript 3 compatible network printers. USB attached Seiko SLP-620 printer.
Operating environment	Indoor Use (protected from water) 10°C to 30°C. 20% to 70% RH (non-condensing). 0 to 2000m altitude. Pollution degree: 2
Storage environment	2°C to 45°C, 20% to 70% RH (non-condensing) for at least 7 days.

© 01/2016 Medix Biochemica. All rights reserved. Actim is a registered trademark of Medix Biochemica.